

After completing the information on this card, tear it off and file it for an instant record of your cassette library's contents.



TAPES TO TAPE		DISK		BROADCAST	
Noise Reduction		BIAS/EO		MONO/STEREO	
<input type="checkbox"/> IN <input type="checkbox"/> OUT		TIME		DATE	
TITLE			NO.		

RECORDING MEMORANDUM

32K Dungeon Adventure

A Noise Reduction
 EO Normal: 120 μ s

B Noise Reduction
 EO Normal: 120 μ s

Copyright (C) Level 9 Computing



32K Dungeon Adventure

NO.

LOW NOISE HIGH OUTPUT

Precision Cassette Mechanism

 **TDK**®

Normal Position **D46**

MADE IN JAPAN



©1982 TDK ELECTRONICS CO., LTD.

Unit 5, Level B South, 100 Harris Street, Plympton, N.S.W. 2009 Australia
TDK (AUSTRALIA) PTY. LTD.
Pembroke House, 44 Wellesley Road, Croydon, Surrey, CR0 9XW, U.K.
TDK TAPE DISTRIBUTOR (U.K.) Limited
13-1, Nishinobashi 1-chome, Chuo-ku Tokyo 103, Japan
TDK ELECTRONICS CO., LTD.

TDK Cassettes are manufactured and shipped under the strictest quality control standards. If this product proves to be defective in materials or workmanship, it will be replaced. This warranty does not affect the statutory rights of the consumer. (Effected only in U.K.)
Note: TDK will not be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use, this product.

TDK D cassettes equal or exceed the performance of premium normal bias cassettes costing much more. The High Grained Ferric Oxide used in TDK D delivers a flat frequency response with excellent high end linearity. TDK D is perfect for general purpose music and speech recording on all types of home, portable, and car decks.

TDK D 46 (69m) 46min.
@ 1-7/8ips (2 x 23min.)

Normal Bias: Normal
(TYPE I)
EQ-120/μs
Tape Selector

D DYNAMIC CASSETTE

PRECISION CASSETTE MECHANISM

The TDK Precision Cassette Mechanism features matched shell halves and bubble surface liner sheets for smooth tape running and even winding. A resiliently mounted pressure pad, tapered and flanged seamless guide rollers mounted on stainless steel pins, and a unique double clamp and hub assembly all combine to provide exact tape alignment.

Tips on Handling and Storage

1. Avoid touching the tape with your fingers; you may cause drop-outs or scratches.
2. Protect your cassette from dust and damage when not in use by keeping it in its protective plastic box.
3. The tape should be wound snugly on the cassette reels; if the tape is loose, carefully wind it on to one of the reels by gently turning one of the hubs.
4. Keep the recorder head and pinch roller clean by regular use of a good cassette head cleaner (like TDK's HC-1, head cleaner cassette).
5. Avoid prolonged exposure of cassettes to excessive heat (should be kept below 110°F/45°C), humidity, direct sunlight and strong magnetic fields. Do not store near heating appliances, TV sets or similar equipment.
6. To preserve valuable or prized recordings, punch out and remove the erasure prevention lug on the top edge of the cassette.